

PRODUCT SPECIFICATION

Recessed roll paper towel dispenser and waste receptacle, Bobrick Model B-3961.

Recessed roll paper towel dispenser and waste receptacle shall be constructed of type-304 stainless steel with satin finish and all-welded construction. Flange shall be 22-gauge (0.8 mm), drawn and beveled, one-piece, seamless construction. Cabinet shall be equipped with an interior stainless steel shelf. Door shall be 18-gauge (1.2-mm) stainless steel and shall be secured to cabinet with a full-length, stainless steel piano hinge and equipped with two tumbler locks. Roll paper towel mechanism shall be adjustable to dispense preset lengths of towels from 1-1/2" (38-mm) standard core diameter rolls 8" (203-mm) to 9" (229-mm) wide and one stub roll up to 4" (102-mm) wide. Roll paper towel mechanism shall have automatic towel transfer system to dispense towels from stub roll before new roll starts to dispense. Lever shall be operable with one hand and with less than 5 lb (22.2 N) force to comply with ADA Accessibility Guidelines (ADAAG). Removable stainless steel waste receptacle shall be equipped with a tumbler lock. Front and side edges of bottom and all top edges of waste receptacle shall be hemmed; unhemmed edges are not acceptable. Waste receptacle minimum capacity: 12 gal. (45.5 liters). Manufacturer's service and parts manual shall be provided to building owner/manager upon completion of project.

