

## CA-3 and DA-3 POT AND PAN WASHERS



CA-3



DA-3

### DESIGN

Automatic door type utensil washer with a timed wash-and-rinse cycle. Fully automatic operation with power on/off button. CA-3 capacity is 25- 24" X 28" racks per hour, or 150 bun pans/hr or 100 steam table (2" thick) pans/hr. DA-3 capacity is 50 - 24" X 28" racks per hour, or 276 bun pans/hr or 184 steam table (2" thick) pans/hr. Cycle starts when doors are closed. Designed for straight through operation. CA-3 is available for corner operation.

### STANDARD EQUIPMENT

- Tank heat: 5 KW electric immersion heater or steam injector
- Capillary thermometer for wash and final rinse
- Vacuum breaker on all incoming water lines
- Rack assortment (CA-3: 1 general utility, 1 bake sheet, 1 basket) (DA-3: 2 general utility, 2 bake sheets, 1 basket, 1 counter pan)
- Manifold cleanout brush
- Inspection door
- Vent opening with adjustable damper (1 for CA-3, 2 for DA-3)
- SureFire™ Start-Up and Check-Out Service
- Door safety switches
- Single point electrical connection: motor, controls, and heater
- S/S frame, legs and feet
- Automatic tank fill
- Low water protection
- Detergent connection provision
- Hold down grid
- Rollers for track on DA-3
- Fully automatic operation
- Manual bypass selector switch
- Side mounted control panel (NEMA 12)
- Simplified scrap screen design
- Interchangeable upper & lower spray arms
- Standard frame drip proof motor

### OPTIONAL ACCESSORY EQUIPMENT

- Stainless steel steam coil tank heat
- Pressure reduction valve and line strainer
- Steam booster
- Electric booster
- Security package
- S/S front panel
- Totally enclosed motor



