

FREEZERS

MODEL	SWING DOORS	CU. FT.	# OF SHELVES	HP	AMPS	CRATED WEIGHT	CABINET DIMENSIONS		
							L	D†	H
GDM-5F	1	5	2	1/2	9.8	210	24	x 23 ¹ / ₂	x 37 ⁵ / ₈
GDM-7F	1	7	3	1/2	11.1	230	24	x 24 ³ / ₄	x 39 ³ / ₄
GDM-10F	1	10	3	1/3	6.4	250	24 ⁷ / ₈	x 23 ¹ / ₈	x 53 ¹ / ₂
GDM-12F	1	12	3	1/3	6.4	300	24 ⁷ / ₈	x 23 ³ / ₈	x 62 ³ / ₈
GDM-23F	1	23	4	3/4	13.0	385	27	x 29 ¹ / ₂	x 78 ¹ / ₄
GDM-26F	1	26	4	3/4	13.0	395	30	x 29 ¹ / ₂	x 78 ¹ / ₄
GDM-35F †	2	35	8	1	9.5	545	39 ¹ / ₂	x 29 ¹ / ₂	x 78 ¹ / ₄
GDM-35SL-F	2	17.1	8	1/2	10.9	375	39 ¹ / ₂	x 23 ¹ / ₄	x 59 ³ / ₈
GDM-43F †	2	40.6	8	1	12.6	585	47	x 29 ¹ / ₂	x 78 ¹ / ₄
GDM-49F †	2	49	8	1 ¹ / ₂	12.9	610	54	x 29 ¹ / ₂	x 78 ¹ / ₄
GDM-72F †	3	72	12	1 ¹ / ₂	12.7	870	78 ¹ / ₄	x 29 ¹ / ₂	x 79 ¹ / ₄

Black and rosewood vinyl exterior available at no extra charge.
 † Depth does not include 1³/₈" for door handle.
 † Depth does not include 1" for rear bumpers on GDM-10F & GDM-12F.
 ‡ Requires 115/208-230/60 Hz, single phase, 3 pole, 4 wire circuit.
 note: GDM-12F height does not include 1" for door hinge.



GDM-12F

PASS-THRU FREEZER

MODEL	SWING DOORS	CU. FT.	# OF SHELVES	HP	AMPS	CRATED WEIGHT	CABINET DIMENSIONS		
							L	D†	H
GDM-5F-PT	2	5	2	1/2	9.4	220	24	x 23 ¹ / ₈	x 37 ⁵ / ₈

Black and rosewood vinyl exterior available at no extra charge.
 † Depth does not include 1³/₈" for door handle (front and back).



GDM-35F



GDM-72F

*The World's Largest
 Manufacturer Of
 Glass Door
 Merchandisers*

FEATURES/BENEFITS

- Oversized, environmentally friendly (404A) refrigeration system, factory sealed and prelubricated for long life.
- -10°F temperature (air off evaporator coil, -20°F. An ideal -10°F for storage of frozen food and ice cream).
- Exterior, durable and permanent non-peel or chip white laminated vinyl (rosewood available - no charge; stainless steel available - extra charge).
- Interior - attractive, NSF approved, white aluminum with 300 series stainless steel floor.
- Standard backguard and floor rack improve airflow (excludes GDM-5F-PT).
- Energy efficient, triple pane, thermal insulated glass doors.
- Adjustable PVC coated wire shelves.
- Safety shielded fluorescent interior lighting for longer, brighter, shadow-free illumination.
- Integrated door light (IDL) standard on swing door models (excludes GDM-5F-PT, GDM-7F, GDM-10F & GDM-12F).
- Foamed-in-place polyurethane high density cell insulation (CFC Free).
- Automatic defrost system time-initiated, temperature-terminated (GDM-5F, GDM-5F-PT & GDM-7F time-initiated, time-terminated).
- Automatic evaporator fan motor delay during defrost cycle.
- Large evaporator and coil heater permit short defrost cycle.
- Illuminated sign panel included (decal on GDM-7F, GDM-10F & GDM-12F).
- Self-contained system, no plumbing required.
- Bottom mount heavy duty compressor, easy access to service.
- Upright freezers are more effective than spot merchandisers because of their high profile visibility.
- Available with optional legs or 2¹/₂" diameter castors. (legs not available on GDM-5F-PT, GDM-10F & GDM-12F; castors not available on GDM-5F-PT & GDM-7F). GDM-7F standard with 2¹/₂" legs; leg levelers standard for all other models shown.
- Optional black interiors available. Upcharge and lead times will apply.
- See our website www.truemfg.com for the latest color & sign offerings.

Remote cabinets and condensing units available for models GDM-23F, GDM-49F and GDM-72F (see pg. 132).

For other models remote cabinets available 14% off list, unavailable for GDM-5F, GDM-5F-PT & GDM-7F. (condensing units supplied by others; system comes standard with 404A expansion valve and requires R404A refrigerant). Consult factory technical service dept. for BTU information.