

DUAL TEMPERATURE

MODEL	SWING DOORS	Cu. Ft.		# OF SHELVES	HP REF - FRZR	AMPS (AT 115V)	CRATED WEIGHT	CABINET DIMENSIONS		
		REF	FRZR					L	D†	H
GDM-49DT ‡	2	23	23	8	1/3 3/4	14.2	595	54	29 1/2	78 1/4

Black and rosewood vinyl exterior available at no extra charge.
 † Depth does not include 1 3/8" for door handle.
 ‡ Requires 115/208-230/60 Hz, single phase, 3 pole, 4 wire circuit.



GDM-49DT

FEATURES/BENEFITS

- Oversized, environmentally friendly refrigeration systems, factory sealed and prelubricated for long life.
- Dual temperature for zoned refrigeration equipped with two, self-contained, independent refrigeration systems.
- Left side refrigerator (134A) maintains 33°F to 38°F temperatures.
- Right side freezer (404A) maintains -10°F temperatures.
- Exterior, durable and permanent non-peel or chip white laminated vinyl (stainless steel available - extra charge).
- Interior - attractive, NSF approved, white aluminum with 300 series stainless steel floor.
- Safety shielded fluorescent interior lighting for longer, brighter, shadow-free illumination.
- 4" CFC free insulated partition between cabinet sections ensures temperature integrity of each product zone.
- Energy efficient, thermal insulated glass doors.
- Adjustable, heavy duty, PVC coated wire shelves.
- Foamed-in-place polyurethane high density cell insulation (CFC Free).
- Illuminated sign panel included.
- Positive seal self-closing doors.
- Minimum wattage heater in cabinet frame and freezer door.
- Self-contained system, no plumbing required.
- Bottom mount heavy duty compressors, easy access to service.
- Optional black interiors available. Upcharge and lead times will apply.
- See our website www.truemfg.com for the latest color & sign offerings.
- **Freezer Compartment Has...**
- Automatic defrost system time-initiated, temperature-terminated.
- Automatic evaporator fan motor delay during defrost cycle.
- Standard backguard and floor rack improve airflow.
- Available with optional legs or 2 1/2" diameter castors.

Remote cabinets available 14% off list (condensing units supplied by others; system comes standard with 404A expansion valve and requires R404A refrigerant). Consult factory technical service dept. for BTU information.