

RADIUS FRONT REFRIGERATORS

MODEL	SWING DOORS	CU. FT.	# OF SHELVES	HP	AMPS	CRATED WEIGHT	CABINET DIMENSIONS		
							L	D†	H
GDM-10RF	1	10	3	1/5	5.0	205	24 ⁷ / ₈	25	53 ¹ / ₂
GDM-12RF	1	12	3	1/5	5.0	220	24 ⁷ / ₈	25	62 ³ / ₈
GDM-14RF	2	14	3	1/3	7.9	295	30 ³ / ₈	29 ¹ / ₄	58
GDM-23RF	1	23	4	1/3	7.2	305	27	31 ¹ / ₄	78 ¹ / ₄
GDM-23FC-RF	1	23	2	1/3	7.5	310	27	31 ¹ / ₄	78 ¹ / ₄
GDM-26RF	1	26	4	1/3	7.2	325	30	31 ¹ / ₄	78 ¹ / ₄
GDM-35RF	2	35	4	1/2	9.2	415	39 ¹ / ₂	32 ³ / ₄	78 ¹ / ₄
GDM-35SL-RF	2	16.4	4	1/3	7.7	250	39 ¹ / ₂	24 ¹ / ₄	58
GDM-49RF	2	49	8	1/2	7.2	495	54	34 ³ / ₄	78 ¹ / ₄

Black and rosewood vinyl exterior available at no extra charge.
 † Depth does not include 1³/₈" for door handles on two door models (excludes GDM-35SL-RF).
 ‡ Depth does not include 1" for rear bumpers on GDM-10RF & GDM-12RF.
 note: GDM-14RF height does not include ⁵/₈" for appliance rollers.



GDM-12RF

True's "Low-E" glass is the latest in energy efficient technology - "Low-E" double pane glass reflects UV rays and provides improved insulation resulting in decreased compressor run time, reducing your energy costs.



GDM-49RF



GDM-26RF

FEATURES/BENEFITS

- Oversized, environmentally friendly (134A) refrigeration - holds 33°F to 38°F.
- Exterior - durable and permanent non-peel or chip white laminated vinyl.
- Interior - attractive, NSF approved, white aluminum with 300 series stainless steel floor.
- Positive seal self-closing doors.
- Energy efficient, "Low-E", thermal insulated glass doors.
- Foamed-in-place polyurethane high density cell insulation (CFC Free).
- Adjustable, heavy duty, PVC coated wire shelves - 10 mil thick, pure grade vinyl coating.
- Safety shielded fluorescent interior lighting for longer, brighter, shadow-free illumination.
- Integrated door light (IDL) standard (excludes GDM-14RF & GDM-35SL-RF).
- Illuminated sign panel included (decal on GDM-10RF, GDM-12RF).
- GDM-14RF standard with 1" diameter appliance rollers (castors and legs not available).
- Self-contained system, no plumbing required.
- Available with optional legs or 2¹/₂" diameter castors (legs not available on GDM-10RF or GDM-12RF).
- GDM-35SL-RF standard with recessed handles; optional door locks available.
- Energy efficient.
- Bottom mount compressor.
- Optional black interiors available. Upcharge and lead times will apply.
- See our website www.truemfg.com for the latest color & sign offerings.

Bottom Mounted Units Have...

- A "no-stoop", lower shelf.
- Allows for top storage.
- Compressor can be serviced easily, and accessed by a single repairman.

Remote cabinets available 14% off list, unavailable for GDM-14RF. (condensing units supplied by others; system comes standard with 404A expansion valve and requires R404A refrigerant).
 Consult factory technical service dept. for BTU information.