

PASS-THRU REFRIGERATORS (FRONT & REAR SOLID DOORS)



TA1RPT-1S-1S



TA2RPT-2S-2S

True's TA Series 1 and 2 section pass-thru refrigerators can be built with any combination of half & full doors in both stainless steel and glass. Please contact your local True representative for nomenclature, pricing and lead times.

Model	Swing Doors	Cu. Ft.	HP	Amps	Crated Weight	Cabinet Dimensions L D H*
SOLID FRONT/SOLID REAR DOORS						
TA1RPT-1S-1S	2	31	1/2	10.4	370	29 x 37 ¹ / ₄ x 78 ¹ / ₄
TA2RPT-2S-2S	4	56	3/4	15.5	710	51 ³ / ₈ x 37 ¹ / ₄ x 78 ¹ / ₄
SOLID FRONT HALF DOORS/SOLID REAR DOORS						
TA1RPT-2HS-1S	3	31	1/2	10.4	535	29 x 37 ¹ / ₄ x 78 ¹ / ₄
TA2RPT-4HS-2S	6	56	3/4	15.5	N/A	51 ³ / ₈ x 37 ¹ / ₄ x 78 ¹ / ₄

* Height does not include 5" for castor height or 6" for optional legs or 1" for mechanical components.

PASS-THRU REFRIGERATORS (SOLID REAR DOORS)

Model	Swing Doors	Cu. Ft.	HP	Amps	Crated Weight	Cabinet Dimensions L D† H*
GLASS FRONT/SOLID REAR DOORS						
TA1RPT-1G-1S	2	31	1/2	10.4	525	29 x 37 ¹ / ₂ x 78 ¹ / ₄
TA2RPT-2G-2S	4	56	3/4	15.5	N/A	51 ³ / ₈ x 37 ¹ / ₂ x 78 ¹ / ₄
GLASS FRONT HALF DOORS/SOLID REAR DOORS						
TA1RPT-2HG-1S	3	31	1/2	10.4	N/A	29 x 37 ¹ / ₂ x 78 ¹ / ₄
TA2RPT-4HG-2S	6	56	3/4	15.5	N/A	51 ³ / ₈ x 37 ¹ / ₂ x 78 ¹ / ₄
COMBINATION FRONT HALF DOORS/SOLID REAR DOORS						
TA1RPT-1HG/1HS-1S	3	31	1/2	10.4	N/A	29 x 37 ¹ / ₂ x 78 ¹ / ₄
TA2RPT-2HG/2HS-2S	6	56	3/4	15.5	N/A	51 ³ / ₈ x 37 ¹ / ₂ x 78 ¹ / ₄

† Depth does not include 1³/₈" for door handles (glass door models only).

* Height does not include 5" for castor height or 6" for optional legs or 1" for mechanical components.

PASS-THRU REFRIGERATORS (GLASS REAR DOORS)

Model	Swing Doors	Cu. Ft.	HP	Amps	Crated Weight	Cabinet Dimensions L D† H*
SOLID FRONT/GLASS REAR DOORS						
TA1RPT-1S-1G	2	31	1/2	10.4	525	29 x 37 ¹ / ₂ x 78 ¹ / ₄
TA2RPT-2S-2G	4	56	3/4	15.5	N/A	51 ³ / ₈ x 37 ¹ / ₂ x 78 ¹ / ₄
SOLID FRONT HALF DOORS/GLASS REAR DOORS						
TA1RPT-2HS-1G	3	31	1/2	10.4	N/A	29 x 37 ¹ / ₂ x 78 ¹ / ₄
TA2RPT-4HS-2G	6	56	3/4	15.5	N/A	51 ³ / ₈ x 37 ¹ / ₂ x 78 ¹ / ₄
GLASS FRONT/GLASS REAR DOORS						
TA1RPT-1G-1G	2	31	1/2	10.4	440	29 x 37 ⁵ / ₈ x 78 ¹ / ₄
TA2RPT-2G-2G	4	56	3/4	15.5	740	51 ³ / ₈ x 37 ⁵ / ₈ x 78 ¹ / ₄
GLASS FRONT HALF DOORS/GLASS REAR DOORS						
TA1RPT-2HG-1G	3	31	1/2	10.4	N/A	29 x 37 ⁵ / ₈ x 78 ¹ / ₄
TA2RPT-4HG-2G	6	56	3/4	15.5	N/A	51 ³ / ₈ x 37 ⁵ / ₈ x 78 ¹ / ₄
COMBINATION FRONT HALF DOORS/GLASS REAR DOORS						
TA1RPT-1HG/1HS-1G	3	31	1/2	10.4	N/A	29 x 37 ⁵ / ₈ x 78 ¹ / ₄
TA2RPT-2HG/2HS-2G	6	56	3/4	15.5	N/A	51 ³ / ₈ x 37 ⁵ / ₈ x 78 ¹ / ₄

† Depth does not include 1³/₈" for glass door handles, front or back.

* Height does not include 5" for castor height or 6" for optional legs or 1" for mechanical components.

FEATURES/BENEFITS

- Shelving - (3) heavy duty, PVC coated wire shelves per section (4) different interior kits available.
- Oversized and balanced, environmentally friendly, refrigeration system, factory sealed and pre-lubricated for long life.
- Food safe refrigerators hold 33°F to 38°F.
- Exterior, digital temperature display.
- Exterior - 300 series stainless steel front, sides, bottom and back (the finest stainless available).
- Interior - attractive, NSF approved, white aluminum sides and back. 300 series stainless floor and solid door liner.
- The utility of the "TA" series pass-thru is in its ability to be a server station for cold dishes. Designed to become a central station, rear-loaded from the kitchen prep area to be front-accessed by servers.
- Foamed-in-place polyurethane high density cell insulation (CFC free).
- Lifetime guaranteed recessed door handles.
- Door locks standard.
- Positive seal self-closing doors with 120 degree stay open feature. Lifetime guaranteed door hinges.
- Incandescent interior lighting on solid door models. Fluorescent interior lighting on glass & combo door models.
- Extruded, aluminum door frames on glass doors.
- Energy efficient, "Low-E", thermal insulated glass on glass doors.
- 4" diameter swivel castors standard equipment. 6" legs available.
- Hot gas condensate for energy efficiency.
- Top mounted unit positioned out of food zone to maximize storage capacity.
- Refrigerator models feature glass condensate pan to prevent electrolysis.
- Self-contained system.

Curb mountable units for TR, TA & TG series only. (5% list upcharge)

Remote cabinets available 14% off list (condensing units supplied by others; system comes standard with 404A expansion valve and requires R404A refrigerant). Consult factory technical service dept. for BTU information.