

ROLL-IN REFRIGERATORS

MODEL	SWING DOORS	CU. FT.	HP	AMPS	CRATED WEIGHT	CABINET DIMENSIONS L D† H*		
SOLID DOORS								
TA1RRI-1S	1	37	1/3	8.9	400	35	34 1/2	83 3/4
TA2RRI-2S	2	75	1/2	11.8	706	68	34 1/2	83 3/4
GLASS DOOR								
TA1RRI-1G	1	37	1/3	8.9	N/A	35	34 3/4	83 3/4
TA2RRI-2G	2	75	1/2	11.8	N/A	68	34 3/4	83 3/4
SOLID DOORS 89" HIGH								
TA1RRI89-1S	1	38	1/3	8.9	485	35	34 1/2	89
TA2RRI89-2S	2	80	1/2	11.8	786	68	34 1/2	89

† Depth does not include 4 1/4" for ramps.

* Height does not include 1" for system mechanical components.



TA1RRI89-1S

ROLL-THRU REFRIGERATORS

MODEL	SWING DOORS	CU. FT.	HP	AMPS	CRATED WEIGHT	CABINET DIMENSIONS L D† H*		
SOLID DOORS								
TA1RRT-1S-1S	2	37	1/3	8.9	475	35	36 7/8	83 3/4
TA2RRT-2S-2S	4	75	1/2	9.5	781	68	36 7/8	83 3/4
GLASS FRONT/SOLID REAR DOOR								
TA1RRT-1G-1S	2	37	1/3	8.9	N/A	35	37 1/8	83 3/4
TA2RRT-2G-2S	4	75	1/2	9.5	N/A	68	37 1/8	83 3/4
SOLID DOORS 89" HIGH								
TA1RRT89-1S-1S	2	38	1/3	8.9	495	35	36 7/8	89
TA2RRT89-2S-2S	4	80	1/2	9.5	821	68	36 7/8	89

† Depth does not include 4 1/4" for ramps (each side).

* Height does not include 1" for system mechanical components.



TA2RRT-2S-2S



TA1RRI-1S

The new consultant choice for roll-in & roll-thru rack applications.

Roll-thru models feature front and rear swing doors, each with a heavy duty stainless steel ramp for roll-thru service.

FEATURES/BENEFITS

- Oversized and balanced, environmentally friendly, refrigeration system, factory sealed and pre-lubricated for long life.
- Food safe refrigerators hold 33°F to 38°F.
- Accepts roll-in rack (inboard castor) with maximum dimensions of 27"W x 29"D x 66"H. 89" high models accept roll-in/thru rack (inboard castor) with maximum dimensions of 27"W x 29"D x 72"H (supplied by others).
- Exterior - 300 series stainless steel solid doors, front, back & bottom. Stainless steel sides.
- Heavy gauge doors.
- Interior - attractive, NSF approved, white aluminum sides and back. 300 series stainless floor and solid door liner.
- Three rugged cam-lift hinges per door, lifetime guaranteed. Designed for easy product access with a full 180 degree open capability and stay open feature at 120 degrees.
- Heavy gauge stainless steel ramp standard for each door.
- Exterior, digital temperature display.
- Interior bumpers protect cabinet walls from abuse caused by roll-in carts.
- Foamed-in-place polyurethane high density cell insulation (CFC Free).
- Incandescent interior lighting.
- Energy efficient, "Low-E", thermal insulated glass on glass doors.
- Energy saver switch.
- Lifetime guaranteed recessed door handles.
- Door locks standard.
- Top mounted unit positioned out of food zone to maximize storage capacity.
- Hot gas condensate for energy efficiency.
- Self-contained system.
- Wiper gaskets for positive seal, reversible.
- Field reversible door swing.
- Reverse front and rear door configurations available on roll-thru models at no charge.

Remote cabinets available 14% off list (condensing units supplied by others; system comes standard with 404A expansion valve and requires R404A refrigerant). Consult factory technical service dept. for BTU information.