

ROLL-IN HEATED CABINETS

MODEL	SWING DOORS	CU. FT.	WATTS	CRATED WEIGHT	CABINET DIMENSIONS		
					L	D†	H*
SOLID DOORS							
TA1HRI-1S ‡	1	37	2000	325	35 x 34 ¹ / ₂	x 83 ³ / ₄	
TA2HRI-2S ‡	2	75	4000	615	68 x 34 ¹ / ₂	x 83 ³ / ₄	
SOLID DOORS 89" HIGH							
TA1HRI89-1S ‡	1	38	2000	385	35 x 34 ¹ / ₂	x 89	

† Depth does not include 4¹/₄" for ramps.

* Height does not include 1" for system mechanical components.

‡ Requires 115/208-240/60 Hz, single phase, 3 pole, 4 wire circuit.

note: TA2HRI-2S requires hard wiring.

ROLL-THRU HEATED CABINETS

MODEL	SWING DOORS	CU. FT.	WATTS	CRATED WEIGHT	CABINET DIMENSIONS		
					L	D†	H*
SOLID DOORS							
TA1HRT-1S-1S ‡	2	37	2000	400	35 x 36 ⁷ / ₈	x 83 ³ / ₄	
TA2HRT-2S-2S ‡	4	75	4000	706	68 x 36 ⁷ / ₈	x 83 ³ / ₄	
SOLID DOORS 89" HIGH							
TA1HRT89-1S-1S ‡	2	38	2000	500	35 x 36 ⁷ / ₈	x 89	

† Depth does not include 4¹/₄" for ramps (each side).

* Height does not include 1" for system mechanical components.

‡ Requires 115/208-240/60 Hz, single phase, 3 pole, 4 wire circuit.

note: TA2HRT-2S-2S requires hard wiring.



TA1HRT89-1S-1S



TA2HRT-2S-2S



TA1HRI-1S

True Heated Cabinets are designed to hold warm baked or cooked food. Cabinets are not designed to heat ambient or cold product.

FEATURES/BENEFITS

- Powerfully provides holding temperatures of 80°F to 180°F throughout the cabinet for uniform, forced-air, heating.
- Low velocity fan(s) provided to assure even temperature throughout cabinet. A vent is located at the top of the cabinet for positive humidity control.
- Heater - stainless steel for corrosion resistance.
- Accepts roll-in rack (inboard castor) with maximum dimensions of 27"W x 29"D x 66"H. TA1HRI89-1S and TA1HRT89-1S-1S accepts roll-in rack (inboard castor) with maximum dimensions of 27"W x 29"D x 72"H (supplied by others).
- Exterior - 300 series stainless steel doors, front, back & bottom. Stainless steel sides.
- Anodized aluminum interior.
- Humidity control - 12" x 20" pan standard.
- Manual humidity control is a standard feature (turn counterclockwise to ventilate).
- Heavy gauge doors.
- Three rugged cam-lift hinges per door- lifetime guaranteed. Designed for easy product access with a full 180 degree open capability and stay open feature at 120 degrees.
- Heavy gauge stainless steel ramp standard for each door.
- Foamed-in-place polyurethane high density cell insulation (CFC Free).
- Exterior, color coded, temperature display.
- Lifetime guaranteed recessed door handles.
- Door locks standard.
- Incandescent interior lighting.
- Self-contained system.
- Wiper gaskets for positive seal, reversible.
- Interior bumpers protect cabinet walls from abuse caused by roll-in carts.
- Field reversible door swing.
- Roll-thru heated cabinet designed to be rear-loaded from prep area and front accessed.