

## ROLL-THRU REFRIGERATORS



TG1RRT89-1S-1S

MODEL	SWING DOORS	CU. FT.	HP	AMPS	CRATED WEIGHT	CABINET DIMENSIONS L D† H*
<b>SOLID DOORS</b>						
TG1RRT-1S-1S	2	37	1/3	8.9	475	35 x 36 <sup>7</sup> / <sub>8</sub> x 83 <sup>3</sup> / <sub>4</sub>
TG2RRT-2S-2S	4	75	1/2	9.5	781	68 x 36 <sup>7</sup> / <sub>8</sub> x 83 <sup>3</sup> / <sub>4</sub>
<b>GLASS FRONT/SOLID REAR DOOR</b>						
TG1RRT-1G-1S	2	37	1/3	8.9	N/A	35 x 37 <sup>1</sup> / <sub>8</sub> x 83 <sup>3</sup> / <sub>4</sub>
TG2RRT-2G-2S	4	75	1/2	9.5	N/A	68 x 37 <sup>1</sup> / <sub>8</sub> x 83 <sup>3</sup> / <sub>4</sub>
<b>SOLID DOORS 89" HIGH</b>						
TG1RRT89-1S-1S	2	38	1/3	8.9	495	35 x 36 <sup>7</sup> / <sub>8</sub> x 89
TG2RRT89-2S-2S	4	80	1/2	9.5	821	68 x 36 <sup>7</sup> / <sub>8</sub> x 89

NEW

† Depth does not include 4<sup>1</sup>/<sub>4</sub>" for ramps (each side).

\* Height does not include 1" for system mechanical components.



TG2RRT-2S-2S

Roll-thru models feature front and rear swing doors, each with a heavy duty stainless steel ramp for roll-thru service.

### FEATURES/BENEFITS

- Oversized and balanced, environmentally friendly, refrigeration system, factory sealed and pre-lubricated for long life.
- Food safe refrigerators hold 33°F to 38°F.
- Accepts roll-in rack (inboard castor) with maximum dimensions of 27"W x 29"D x 66"H. TG1RRT89-1S-1S and TG2RRT89-2S-2S accept roll-in rack (inboard castor) with maximum dimensions of 27"W x 29"D x 72"H (supplied by others).
- 300 series stainless steel solid doors and rain-shield (the finest stainless available).
- Anodized quality aluminum sides, bottom and back.
- Interior - attractive, NSF approved, white aluminum sides. 300 series stainless floor and solid door liner.
- Heavy gauge doors.
- Field reversible door swing.
- Lifetime guaranteed recessed door handles.
- Door locks standard.
- Three rugged cam-lift hinges per door, lifetime guaranteed. Designed for easy product access with a full 180 degree open capability and stay open feature at 120 degrees.
- Exterior, digital temperature display.
- Incandescent interior lighting.
- Energy efficient, "Low-E", thermal insulated glass on glass doors.
- Interior bumpers protect cabinet walls from abuse caused by roll-in carts.
- Foamed-in-place polyurethane high density cell insulation (CFC Free).
- Hot gas condensate for energy efficiency.
- Energy saver switch.
- Heavy gauge stainless steel ramp standard for each door.
- Top mounted unit positioned out of food zone to maximize storage capacity.
- Self-contained system.
- Wiper gaskets for positive seal, reversible.
- Reverse front and rear door configurations available on roll-thru models at no charge.

Remote cabinets available 14% off list (condensing units supplied by others; system comes standard with 404A expansion valve and requires R404A refrigerant). Consult factory technical service dept. for BTU information.