



TG2F-2G

REACH-IN FREEZERS

MODEL	SWING DOORS	Cu. Ft.	HP	AMPS	CRATED WEIGHT	CABINET DIMENSIONS L D† H*
SOLID DOORS						
TG1F-1S	1 s/s	31	1/2	10.8	410	29 x 34 ³ / ₄ x 78 ¹ / ₄
TG2F-2S	2 s/s	56	3/4	13.0	704	51 ³ / ₈ x 34 ³ / ₄ x 78 ¹ / ₄
TG3F-3S ‡	3 s/s	85	1 1/2	11.4	790	76 ¹ / ₂ x 34 ³ / ₄ x 78 ¹ / ₄
SOLID HALF DOORS						
TG1F-2HS	2 s/s	31	1/2	10.8	410	29 x 34 ³ / ₄ x 78 ¹ / ₄
TG2F-4HS	4 s/s	56	3/4	13.0	704	51 ³ / ₈ x 34 ³ / ₄ x 78 ¹ / ₄
TG3F-6HS ‡	6 s/s	85	1 1/2	11.4	790	76 ¹ / ₂ x 34 ³ / ₄ x 78 ¹ / ₄
GLASS DOORS						
TG1F-1G	1 g/s	31	3/4	11.5	435	29 x 34 ⁷ / ₈ x 78 ¹ / ₄
TG2F-2G ‡	2 g/s	56	1	9.1	725	51 ³ / ₈ x 34 ⁷ / ₈ x 78 ¹ / ₄

† Depth does not include 1³/₈" for door handles (glass door models only).

* Height does not include 5" for castor height or 6" for optional legs.

* Height does not include 1" for system mechanical components.

‡ Requires 115/208-230/60 Hz, single phase, 3 pole, 4 wire circuit.

PASS-THRU FREEZER

MODEL	SWING DOORS	Cu. Ft.	HP	AMPS	CRATED WEIGHT	CABINET DIMENSIONS L D H*
SOLID DOORS						
TG2FPT-2S-2S ‡	4 s/s	56	1	9.1	754	51 ³ / ₈ x 37 ¹ / ₄ x 78 ¹ / ₄

* Height does not include 5" for castor height or 6" for optional legs.

* Height does not include 1" for system mechanical components.

‡ Requires 115/208-230/60 Hz, single phase, 3 pole, 4 wire circuit.



TG2FPT-2S-2S



TG3F-3S

FEATURES/BENEFITS

- Environmentally friendly (404A), refrigerant.
- Freezer holds -10°F (air off evaporator coil, -20°F) for the best in food preservation.
- Shelving - (3) heavy duty, PVC coated wire shelves per section (4) different interior kits available. See "spec. series" accessory pages 70 or 134 for details (field installation required).
- 300 series stainless steel solid doors and rain-shield (the finest stainless available).
- Anodized quality aluminum sides, bottom and back.
- Interior - attractive, NSF approved, white aluminum sides. 300 series stainless floor and solid door liner.
- Automatic defrost system time-initiated, temperature-terminated.
- Automatic evaporator fan motor delay during defrost cycle.
- Minimum wattage heater in cabinet frame and door.
- Foamed-in-place polyurethane high density cell insulation (CFC free).
- Lifetime guaranteed recessed handles on solid doors.
- Door locks standard.
- Exterior, digital temperature display.
- Positive seal self-closing doors with 120 degree stay open feature (center doors of 3 section models have 90 degree stay open feature). Lifetime guaranteed door hinges.
- Standard backguard improves airflow (excludes pass-thru model).
- 4" diameter swivel castors standard equipment. 6" legs available.
- Incandescent interior lighting on solid door models. Fluorescent interior lighting, integrated door light (IDL) on glass door models.
- Energy efficient, triple pane, thermal insulated glass on glass doors.
- Pass-thru freezer designed to be rear-loaded from prep area and front accessed.
- Top mounted unit positioned out of food zone to maximize storage capacity.
- Self-contained system.

Curb mountable units for TR, TA & TG series only. (5% list upcharge)

Remote cabinets available 14% off list (condensing units supplied by others; system comes standard with 404A expansion valve and requires R404A refrigerant). Consult factory technical service dept. for BTU information.