

SANDWICH/SALAD

MODEL	DOORS/ DRAWERS	CU. FT.	# OF SHELVES	# OF PANS (TOP)	HP	AMPS	CRATED WEIGHT	CABINET DIMENSIONS		
								L	D†	H*
TSSU-27-8 **	1/0	6.5	2	8	1/5	4.9	215	27 ⁵ / ₈	30 ¹ / ₈	36 ³ / ₄
TSSU-36-8	2/0	8.5	4	8	1/3	8.3	240	36 ³ / ₈	30 ¹ / ₈	36 ³ / ₄
TSSU-48-8	2/0	12.0	4	8	1/3	8.6	290	48 ³ / ₈	30 ¹ / ₈	36 ³ / ₄
TSSU-48-10	2/0	12.0	4	10	1/3	8.6	285	48 ³ / ₈	30 ¹ / ₈	36 ³ / ₄
TSSU-48-12	2/0	12.0	4	12	1/3	8.6	285	48 ³ / ₈	30 ¹ / ₈	36 ³ / ₄
TSSU-60-8	2/0	15.5	4	8	1/3	7.8	330	60 ³ / ₈	30 ¹ / ₈	36 ³ / ₄
TSSU-60-10	2/0	15.5	4	10	1/3	7.8	320	60 ³ / ₈	30 ¹ / ₈	36 ³ / ₄
TSSU-60-12	2/0	15.5	4	12	1/3	7.8	330	60 ³ / ₈	30 ¹ / ₈	36 ³ / ₄
TSSU-60-16	2/0	15.5	4	16	1/3	7.8	335	60 ³ / ₈	30 ¹ / ₈	36 ³ / ₄
TSSU-72-8	3/0	19.0	6	8	1/2	10.3	420	72 ³ / ₈	30 ¹ / ₈	36 ³ / ₄
TSSU-72-10	3/0	19.0	6	10	1/2	10.3	420	72 ³ / ₈	30 ¹ / ₈	36 ³ / ₄
TSSU-72-12	3/0	19.0	6	12	1/2	10.3	420	72 ³ / ₈	30 ¹ / ₈	36 ³ / ₄
TSSU-72-16	3/0	19.0	6	16	1/2	10.3	420	72 ³ / ₈	30 ¹ / ₈	36 ³ / ₄
TSSU-72-18	3/0	19.0	6	18	1/2	10.3	405	72 ³ / ₈	30 ¹ / ₈	36 ³ / ₄
DRAWERED										
TSSU-27-8D-2 **	0/2	6.5	N/A	8	1/5	4.9	230	27 ⁵ / ₈	30 ¹ / ₈	36 ³ / ₄
TSSU-48-12D-2	1/2	12.0	2	12	1/3	8.6	325	48 ³ / ₈	30 ¹ / ₈	36 ³ / ₄
TSSU-48-12D-4	0/4	12.0	N/A	12	1/3	8.6	330	48 ³ / ₈	30 ¹ / ₈	36 ³ / ₄
TSSU-60-16D-2	1/2	15.5	2	16	1/3	7.8	380	60 ³ / ₈	30 ¹ / ₈	36 ³ / ₄
TSSU-60-16D-4	0/4	15.5	N/A	16	1/3	7.8	400	60 ³ / ₈	30 ¹ / ₈	36 ³ / ₄

All models listed are available with optional crumb catcher.

All models listed are available with optional 19" cutting board (excludes drawered models).

† Depth does not include 1" for rear bumpers.

* Height does not include 6¹/₄" for castors or 6" for optional legs.

** Length dimension does not include 1/8" (each side) for lid pins, TSSU-27's only.

note: Door/drawer combination cabinets require customer to designate door/drawer orientation.

DUAL SIDED SANDWICH/SALAD

MODEL	DOORS/ DRAWERS	CU. FT.	# OF SHELVES	# OF PANS (TOP)	HP	AMPS	CRATED WEIGHT	CABINET DIMENSIONS		
								L	D	H*
TSSU-60-16-DS-ST	2/0	15.5	4	16	1/3	7.8	375	60 ³ / ₈	38 ³ / ₄	31 ³ / ₈

All models listed are available with optional crumb catcher.

* Height does not include 6¹/₄" for castors or 6" for optional legs.

Pan Configuration



Standard Models:
feature two rows of pans (front to back)
and 11³/₄" cutting board.



TSSU-36-8

Holds 33°F
to 41°F



TSSU-48-12



TSSU-72-12

See
Page 80 For
Alternative Pan
Configurations.

FEATURES/BENEFITS

- Oversized and balanced, environmentally friendly (134A), refrigeration system, with airflow directed at pans for colder temperatures. Guided airflow provides uniform temperature in a 360° circle throughout cabinet for stay-fresh meats and cheeses, and colder crisper salads.
- Holds 33°F to 41°F product temperature in pans.
- All stainless steel front, top and sides.
- Stainless steel patented foam insulated cover keeps pans colder to lock in freshness - minimizes condensation.
- Aluminum finished back.
- Interior - attractive, NSF approved, white aluminum sides and top, coved corners and 300 series stainless steel floor.
- Back hood and lid are removable for cleaning purposes.
- 5" diameter castors standard (legs available).
- Swing doors are self-closing with 90 degree stay open feature.
- Doors swing within cabinet dimensions.
- Recessed handles.
- Extra deep 11³/₄" full length removable cutting board.
- Versatile, sanitary, white polyethylene cutting boards provide tough surface. Large comfortable working area.
- Adjustable, heavy duty, PVC coated wire shelves (not available in drawered models).
- Standard full set of (1/6 size) 6⁷/₈"L x 6¹/₄"W x 4"D NSF approved, clear polycarbonate insert pans included (positioned in countertop). Also accommodates six and eight inch deep pans (drawered models will not accommodate 8" deep condiment pans).
- Foamed-in-place polyurethane high density cell insulation (CFC free).
- Rear bumpers (except dual sided model).
- Available with optional 19" white polyethylene or composite cutting board, crumb catcher or overself (19" cutting boards exclude dual sided & drawered models).
- Front breathing.
- ADA compliant models with 34" work surface height available. (see pg. 78: models -27, -36, -48, -60, -72)
- Effective April 1, 1998 all production of True models comply with NSF-7 rating.

Dual Sided Model Has...

- Food prep access from both sides for high volume access along with the space efficiency of an island prep table.
- Standard with 11³/₄" white polyethylene cutting board.

Drawered Models Have...

- Accommodate one 12"L x 20"W x 6"D pan per drawer (drawer pans are not included). (48" models accommodate one 12"L x 18"W x 6"D food storage box or one 1/3 size and one 1/2 size pan per drawer; not included).
- Door/drawer combination models require customer to designate door/drawer orientation.

Remote cabinets available 14% off list (condensing units supplied by others; system comes standard with 404A expansion valve and requires R404A refrigerant). Consult factory technical service dept. for BTU information.