

WORKTOP REFRIGERATORS

MODEL	DOORS/ DRAWERS	CU. FT.	# OF SHELVES	HP	AMPS	CRATED WEIGHT	CABINET DIMENSIONS		
							L	D†	H*
TWT-27	1/0	6.5	2	1/6	3.9	185	27 ⁵ / ₈	30 ¹ / ₈	33 ³ / ₈
TWT-36	2/0	8.5	4	1/6	4.7	225	36 ³ / ₈	30 ¹ / ₈	33 ³ / ₈
TWT-48	2/0	12.0	4	1/5	5.0	270	48 ³ / ₈	30 ¹ / ₈	33 ³ / ₈
TWT-60	2/0	15.5	4	1/5	5.1	315	60 ³ / ₈	30 ¹ / ₈	33 ³ / ₈
TWT-72	3/0	19.0	6	1/3	8.5	375	72 ³ / ₈	30 ¹ / ₈	33 ³ / ₈
DRAWERED									
TWT-27D-2	0/2	6.5	N/A	1/6	3.9	210	27 ⁵ / ₈	30 ¹ / ₈	33 ³ / ₈
TWT-48D-2	1/2	12.0	2	1/5	5.0	315	48 ³ / ₈	30 ¹ / ₈	33 ³ / ₈
TWT-48D-4	0/4	12.0	N/A	1/5	5.0	325	48 ³ / ₈	30 ¹ / ₈	33 ³ / ₈
TWT-60D-2	1/2	15.5	2	1/5	5.1	370	60 ³ / ₈	30 ¹ / ₈	33 ³ / ₈
TWT-60D-4	0/4	15.5	N/A	1/5	5.1	370	60 ³ / ₈	30 ¹ / ₈	33 ³ / ₈

† Depth does not include 1" for rear bumpers.

* Height does not include 6¹/₄" for castors or 6" for optional legs.

note: Door/drawer combination cabinets require customer to designate door/drawer orientation.



TWT-27D-2

WORKTOP FREEZERS

MODEL	DOORS	CU. FT.	# OF SHELVES	HP	AMPS	CRATED WEIGHT	CABINET DIMENSIONS		
							L	D†	H*
TWT-27F	1	6.5	2	1/3	8.3	190	27 ⁵ / ₈	30 ¹ / ₈	33 ³ / ₈
TWT-48F	2	12.0	4	1/4	6.1	275	48 ³ / ₈	30 ¹ / ₈	33 ³ / ₈
TWT-60F	2	15.5	4	1/2	10.9	355	60 ³ / ₈	30 ¹ / ₈	33 ³ / ₈

† Depth does not include 1" for rear bumpers.

* Height does not include 6¹/₄" for castors or 6" for optional legs.



TWT-36



TWT-60

TWT MODELS
Heavy, 16 Gauge Tops
All TWT-27 models
All TWT-36 models
All TWT-48 models
All TWT-60 models
All TWT-72 models

ADA Compliant Castor Packages Available - See Page 88.

FEATURES/BENEFITS

- Oversized, environmentally friendly refrigeration system (refrigerators: 134A / freezers: 404A).
- Refrigerator holds 33°F to 38°F temperature; freezer holds -10°F.
- Automatic defrost system on freezer models time-initiated, time-terminated.
- 360° circular airflow for uniform product cooling.
- All stainless steel front, top and sides.
- Interior - attractive, NSF approved, white aluminum sides and top, 300 series stainless steel floor with coved corners.
- .040 aluminum finished back minimizes dirt accumulation.
- Recessed handles.
- Work surface 36" high.
- Stainless steel backsplash - one piece formed construction. No bacteria or food particles can be trapped underneath as with other two piece worktop units.
- Adjustable PVC coated wire shelves (not available in drawer models).
- Foamed-in-place high density polyurethane insulation (CFC free).
- 5" diameter castors standard equipment (legs available).
- Front breathing. May be aligned side by side with other units.
- Swing doors are self-closing with 90 degree stay open feature.
- Doors swing within cabinet dimensions.
- Self-contained system.
- ADA compliant models with 34" work surface height available; no charge. (see pg. 88: models -27, -36, -48, -60, -72).
- Heavy, 16 gauge tops available -upcharge applies.

Drawer Models

- Accommodates one 12" L x 20" W x 6" D full size pan or two 1/2 pans or three 1/3 pans per drawer. (48" models accommodate one 12" L x 18" W x 6" D food storage box or one 1/3 size and one 1/2 size pan per drawer; not included).
- Door/drawer combination models require customer to designate door/drawer orientation.

Remote cabinets available 14% off list (condensing units supplied by others; system comes standard with 404A expansion valve and requires R404A refrigerant). Consult factory technical service dept. for BTU information.