

Project _____

Item # _____

Quantity _____



GLOBE FOOD EQUIPMENT COMPANY

Compact Automatic Slicer

GC12BA



GC12BA Compact Automatic Slicer

Chefmate™ Model

GC12BA - Compact Automatic Slicer



Standard Features

- 12" hard chromed, hollow ground knife
- Knife cover interlock
- Top mounted all metal knife sharpener
- Permanently attached knife ring guard
- Powerful 1/2 HP knife motor
- Independent chute motor
- Automatic chute speed of 40 strokes per minute
- Manual or automatic slicer operation
- Anodized aluminum construction with seamless edges and radiused corners
- Large product receiving area
- Smooth ball bearing chute slide
- 35° angled food chute
- 0 to 1/2" slice thickness
- Metal bottom enclosure
- Removable slice deflector
- Motor overload protection
- Power indicator light

Standard Warranty

- 1 year parts and labor

Approved By: _____

Date: _____



GLOBE FOOD EQUIPMENT COMPANY

www.globeslicers.com

2153 Dryden Rd
Dayton, OH 45439
Phone: 937-299-5493
Phone: 800-347-5423
Fax: 937-299-4147



Compact Automatic Slicer

GC12BA

Specifications

Finish: Heavy gauge anodized aluminum that is stain resistant, long lasting, and easy to clean.

Motors: Powerful 1/2 HP knife motor, fan cooled, 115-60-1, 6 amps. Separate chute motor. Both motors have permanently lubricated ball bearings, which ensures quiet operation.

Knife Drive: Knife is driven by a positive grooved belt that works well in medium duty applications.

Slice Thickness: Food can be sliced from 0 to 1/2" thick.

Knife Cover Interlock: Slicer will not operate with the knife cover removed.

Top Mounted Sharpener: Sharpener is made of all metal and is top mounted for easy access. A two stone, dual action design allows you to quickly return a razor sharp edge to your knife.

Hollow Ground Knife: Nominal 12" diameter, hard chromed, hollow ground blade lasts longer and sharpens easier.

On/Off Controls: Moisture protected separate on/off push button type.

Automatic Chute Drive: Chute travels at 40 strokes per minute utilizing a separate motor and linkage drive system. Chute can be quickly engaged or disengaged for manual operation with the auto engage lever located on the front of the slicer.

Ball Bearing Chute Slide System: Ball bearing system ensures smooth and easy movement of the food chute assembly.

Knife Hub: Knife hub bearings, belt, and motor are fully enclosed protecting them from food and other debris.

Knife Ring Guard: Permanently mounted knife ring guard covers the non-slicing portion of the knife protecting the operator from the knife's edge.

Table Rod: Separate table support rod is protected by the table casting and cover.

Underside: Components are covered by a metal plate protecting them from food and other debris.

Slice Deflector: Heavy duty deflector is securely fastened to the slicer, yet is still easy to remove without tools.

Capacity: Width 9.5" (24.1cm), Height 8.5" (21.6cm), Diameter 8" (20.3cm)

Cord & Plug: Attached 6 foot flexible 3 wire cord and plug fits a grounded receptacle.

Dimensions:
Foot Print: 14.875"W x 19.125"D
(37.8cm x 48.6cm)

Overall Length: 24" (61cm)
Overall Width: 19.25" (49cm)
Overall Height: 19.5" (49.5cm)
Freight Class: 77.5
Net Weight: 79.4 lbs. (36kgs.)
Shipping Weight: 122 lbs (55.3kgs.)
Box Dimensions:
25.75"W x 21.5"D x 23.75"H
(64.4cm W x 54.6cm D x 60.3cm H)



GLOBE FOOD EQUIPMENT COMPANY

www.globeslicers.com

2153 Dryden Rd
Dayton, OH 45439
Phone: 937-299-5493
Phone: 800-347-5423
Fax: 937-299-4147

Printed in U.S.A. 11-2007

Specifications are subject to change without notice.